

EXHAUST FAN

Salient Features

- Aerodynamically contoured handle maximum air with minimum power consumption
- Rigid frame with rubber mounting for silent operation
- Epoxy powder coating with specially pretreated components for better resistance to corrosion and acid alkali fumes
- Totally enclosed highly efficient heavy duty motor with pressure die cast aluminium rotor mounted on two ball bearings

| Size (mm) | Size (Inch) | RPM | Capacity | Watts | AMP |
|-----------|-------------|------|----------|-------|------|
| 225 | 9 | 1400 | 1.5mfd | 42 | 0.21 |
| 300 | 12 | 1400 | 2.5mfd | 90 | 0.40 |
| 380 | 15 | 1400 | 4mfd | 160 | 0.77 |
| 450 | 18 | 1400 | 5mfd | 410 | 1.9 |
| 600 | 24 | 1400 | 6mfd | 550 | 2.42 |



MAXI VENTILATING FAN SQUARE



| Size (mm) | Size (Inch) | Speed (RPM) | Air Delivery (M ³ /M) | Rated Power (W) | Rated Frequency (Hz) |
|-----------|-------------|-------------|----------------------------------|-----------------|----------------------|
| 150 | 6 | 1300 | 4.7 | 23 | 50/60 |
| 200 | 8 | 1200 | 8.7 | 28 | 50/60 |
| 250 | 10 | 1100 | 14.3 | 36 | 50/60 |
| 300 | 12 | 1100 | 20 | 45 | 50/60 |

MAXI VENTILATING FAN ROUND



| Size (mm) | Size (Inch) | Speed (RPM) | Air Delivery (M ³ /M) | Power Input (W) | Rated Frequency (Hz) |
|-----------|-------------|-------------|----------------------------------|-----------------|----------------------|
| 150 | 6 | 1950 | 4.3 | 15 | 50/60 |
| 200 | 8 | 2150 | 7 | 20 | 50/60 |



**POWERFUL
MOTOR**




**MOISTURE
PROOF**



**ENERGY
SAVING**



**EFFICIENT
& MUTE**



ULTRA QUIET

Salient Features

- Low Noise
- Large Airflow
- Long-life Motor
- Temperature Control
- Modern Unique Design
- Polypropylene Blades
- Dust Protection Shutters